VT.602H

Our EPD Group 2 - Como Range for Floor & Wall comes in hundreds of different designs, colours, slip ratings and finishes. Much of the range is accredited to rigorous eco-friendly standards (including LEED/BREEAM etc) to help specifiers meet the sustainability goals of their clients.



MOBILE SAMPLE LIBRARY REFERENCE Stone Look Honed Finish EPD Group 2 - Como Range

Honed Properties ISO 9001 Í ISO 14001 BREEAM LEED EMAS R10 40% More Thermal Carbon Chemical Frost Colours Recycled Shock \sim Offset Content Resistant Resistant Resistant Available COMO Other formats Other finishes 20mm Bush Paver Hammered Sizes available 1. 1 1 60cm 11 - H. 100cm I 6mm ‡ ///////// 1. -11 60cm 1. 11 ¥ < -_ _ _ _ _ _ _ 30cm 100cm 60cm н I. 60cm www.ecofriendlytiles.co.uk н Т ECO FRIENDLY < - - - - -</pre> ----_ _ 120cm TILES®

Eco Friendly Tiles Ltd Ground Floor, Solon House 40a Peterborough Road London SW6 3BN

0844 980 2233 info@ecofriendlytiles.co.uk

The planet, covered

Technical Specification Code: VT.602H



Eco Friendly Tiles Ltd Ground Floor, Solon House 40a Peterborough Road London SW6 3BN 0844 980 2233 info@ecofriendlytiles.co.uk

www.ecofriendlytiles.co.uk

Norm/test method	Required Standard	Results
EN ISO 10545-2	± 5.0% Max	± 5.0%
EN ISO 10545-2	±0.6% Max	± 0.1%
EN ISO 10545-2	± 0.5% Max	± 0.1%
EN ISO 10545-2	± 0.5% Max	± 0.1%
EN ISO 10545-2	± 0.5% Max	± 0.2%
EN ISO 10545-3	≤ 0.5%	≤ 0.01%
EN ISO 10545-4	≥ 35 N/mm ²	49 N/mm ²
EN ISO 10545-6	≤ 175 mm ³	140 mm ³
EN ISO 10545-8	-	< 6.5*10 ⁻⁶ °C ⁻¹
EN ISO 10545-9	-	Resistant
EN ISO 10545-12	-	Compliant
EN ISO 10545-13	UB Minimum	A, LA, HA
EN ISO 10545-14	-	Class 5
DIN 51094	-	No change in Brightness or Colour
DIN 51130	-	R10
BS 7976-2:2002 Pendulum	-	-
Decision 96/603 CE	-	A1-A1 _{FL}
	EN ISO 10545-2 EN ISO 10545-2 EN ISO 10545-2 EN ISO 10545-2 EN ISO 10545-2 EN ISO 10545-3 EN ISO 10545-4 EN ISO 10545-4 EN ISO 10545-6 EN ISO 10545-8 EN ISO 10545-9 EN ISO 10545-9 EN ISO 10545-12 EN ISO 10545-13 EN ISO 10545-14 DIN 51094 DIN 51130 BS 7976-2:2002 Pendulum	EN ISO 10545-2 ± 5.0% Max EN ISO 10545-2 ± 0.6% Max EN ISO 10545-2 ± 0.5% Max EN ISO 10545-3 ≤ 0.5% EN ISO 10545-4 ≥ 35 N/mm² EN ISO 10545-6 ≤ 175 mm³ EN ISO 10545-7 - EN ISO 10545-8 - EN ISO 10545-12 - EN ISO 10545-12 - EN ISO 10545-13 UB Minimum EN ISO 10545-14 - DIN 51094 - DIN 51130 - BS 7976-2:2002 Pendulum -

Certifications



This technical information sheet is not a guarantee of performance and is not a warranty, either explicit or implicit. Rather, it tries to summarize for the designer, installer or developer the technical data provided to Eco Friendly Tiles by the independent tile manufacturer. This information may not be applicable in all geographical areas. It is the responsibility of those individuals who are referring to this document to independently research and determine which tiles are suitable for a given project according to applicable British or International Standards and any governing legislative requirements. This document cannot be used as expert opinion, evidence or in any legal or administrative procedure unless authorized by Eco Friendly Tiles Ltd.