


VT.676


Our EPD Group 5 - Alps Range for Floor & Wall comes in hundreds of different designs, colours, slip ratings and finishes. Much of the range is accredited to rigorous eco-friendly standards (including LEED/BREEAM etc) to help specifiers meet the sustainability goals of their clients.
















www.ecofriendlytiles.co.uk

Eco Friendly Tiles Ltd Ground Floor, Solon House 40a Peterborough Road London SW6 3BN

0844 980 2233 info@ecofriendlytiles.co.uk

Technical Specification Code: VT.676



Eco Friendly Tiles Ltd Ground Floor, Solon House 40a Peterborough Road London SW6 3BN

0844 980 2233 info@ecofriendlytiles.co.uk

www.ecofriendlytiles.co.uk

Physical & chemical properties	Norm/test method	Required Standard	Results
Water absorption	EN ISO 10545-3	≤ 0.5%	≤ 0.5%
Breaking Strength	EN ISO 10545-4	≥ 35 N/mm²	50 N/mm²
			1,300 N
Abraision Resistance	EN ISO 10545-6	≤ 175 mm³	123 mm³
Coefficient of Linear Thermal Expansion	EN ISO 10545-8	-	a ≤ 7*10 ⁻⁶ °C ⁻¹
Frost Resistance	EN ISO 10545-12	-	Resistant
Resistance to Chemicals	EN ISO 10545-13	B Minimum	LA-HA Resistant, A Resistant
Resistance to Stains	EN ISO 10545-14	-	5
Slip Resistance	DIN 51130	-	R10
Pendulum Test Value		-	PTV 36+
Fire Reaction	EN 13823/EN 9239-1		Class A1 (wall)/Class A1fl (floor

Certifications













